

7.4 STEREO POWER AMPLIFIER C21

General

Weight	22 kg / 48.5 lbs
Dimensions (without cables)	W 45,0 cm / D 42,7 cm / H 14,5 cm W 17.7 in / D 16.8 in / H 5.7 in
Dimensions with packaging	W 59,0 cm / D 54,0 cm / H 35,5 cm W 23.2 in / D 21.3 in / H 21.9 in
Line Voltage	230 Vac / 50 Hz or 115 Vac / 50/60 Hz (single voltage, factory setting depending on country)
Power consumption	
in stand by	< 0.5 VA
in idle	< 70 VA
Maximum	< 1000 VA (w. 2 x 300 W @ 4 Ohm)

Connections

Inputs	1 x RCA In, unbalanced 1 x XLR In, balanced
Outputs	1 pair Loudspeaker Binding Posts
Other	2 x MBL SmartLink

Specifications

Rated Power	
Stereo 4 Ohm	2 x 300 W
Stereo 8 Ohm	2 x 180 W
Stereo 2 Ohm	2 x 400 W
Peak Output Voltage	62 Vp
Peak Output Current	20 Ap
Input Impedance (RCA / XLR)	9 kOhm/ 18 kOhm
Input Sensitivity (RCA / XLR)	100 mV / 200 mV for 1 W @ 4 Ohm
Rated Input Voltage (RCA / XLR)	1.7 V / 3.4 V for 300 W @ 4 Ohm
Voltage gain (RCA / XLR)	20 (26 dB) / 10 (20 dB)
Absolute Polarity	In-Phase (RCA / XLR Pin 2)
Signal / Noise Ratio @ Rated Output	124 dB (A) @ 300 W / 4 Ohm
Signal / Noise Ratio @ 1 Watt	100 dB (A) @ 1 W / 4 Ohm
Equivalent Input Noise - RCA	126 dB (A) @ 2 V Input
Equivalent Input Noise - XLR	126 dB (A) @ 4 V Input
Frequency Response	< 10 Hz – 45 kHz
Distortion THD+N	Typ. 0.01 % @ 3 W from 20 Hz ... 20 kHz
Damping Factor	> 100 (40 dB) @ 1 kHz / 4 Ohm
Channel Separation	> 100 dB @ 1 kHz