

ZION
O 3 MKII
132"

Physical Parameters	
Pixel Pitch	3 mm
Pixel Configuration	SMD 3-en-1
Configuration (LxH, per screen)	960x576 píxeles
LED Encapsulation	SMD 1415
Dimensions (W x H x D, Screen)	2880X1728X97 mm
Diagonal (inch, per screen)	132
Weight (per screen)	180 kg
Optical Parameters	
Equilibrium Brightness	5500 nits
Contrast Ratio	5500:1
Viewing angle	170°
Bit Depth	8 bits
Color Temperature	6500-10000K
Gray Scale/Colors	16.7M Colors

Electrical Parameters	
Display Working Voltage	AC47~63HZ,220V±15%/110V±15%
Screen - Power consumption - Max	3976 W
Screen - Power consumption - Typical	1242,5 W
Frame frequency	60 Hz
Operation Conditions	
Working Temperature / Humidity	-10~60 °C / 10%~70% RH
IP Rating	IP65
LED Lifetime	100.000 hours
Refresh Rate	3840 Hz
Video Processor	X6
Certification	
CE	
Service	
Rear Only	
Special Installation	
Cabinets installation side by side	
Accessories	
Decorative frame	

ZION
O 3 MKII
183"

Physical Parameters	
Pixel Pitch	3 mm
Pixel Configuration	SMD 3-en-1
Configuration (LxH, per screen)	1344x768 pixels
LED Encapsulation	SMD 1415
Dimensions (W x H x D, per Screen)	4032x2304x97 mm
Diagonal (inch, per screen)	183
Weight (per screen)	336 kg
Optical Parameters	
Equilibrium Brightness	5500 nits
Contrast Ratio	5500:1
Viewing Angle	170°
Bit Depth	8 bits
Color Temperature	6500-10000K
Gray Scale/Colors	16.7M Colors

Electrical Parameters	
Display Working Voltage	AC47~63HZ,220V±15%/110V±15%
Screen - Power Consumption - Max	7424 W
Screen - Power Consumption - Typical	2320 W
Frame Frequency	60 Hz
Operation Conditions	
Working Temperature / Humidity	-10~60 °C / 10%~70% RH
IP Rating	IP65
LED Lifetime	100.000 hours
Refresh Rate	3840 Hz
Video Processor	X6
Certification	
	CE
Service	
	Rear Only
Special Installation	
	Cabinets installation side by side
Accessories	
	Decorative frame