

ZION  
O 4 MKII  
132"

Physical Parameters	
Pixel Pitch	3.9 mm
Pixel Configuration	SMD 3-en-1
Configuration (LxH, per screen)	768x384 píxeles
LED Encapsulation	SMD 1921
Dimensions (W x H x D, Screen)	3000X1500X97 mm
Diagonal (inch, per screen)	132
Weight (per screen)	189 kg
Optical Parameters	
Equilibrium Brightness	5500 nits
Contrast Ratio	5500:1
Viewing angle	170°
Bit Depth	8 bits
Color Temperature	6500-10000K
Gray Scale/Colors	16.7M Colors

Electrical Parameters	
Display Working Voltage	AC47~63HZ,220V±15%/110V±15%
Screen - Power consumption - Max	3600 W
Screen - Power consumption - Typical	1080 W
Frame frequency	60 Hz
Operation Conditions	
Working Temperature / Humidity	-10~60 °C / 10%~70% RH
IP Rating	IP65
LED Lifetime	100.000 hours
Refresh Rate	3840 Hz
Video Processor	X6
Certification	CE
Service	Front with locks
Special Installation	Cabinets installation side by side
Accessories	Decorative frame

ZION  
O 4 MKII  
186"

<b>Physical Parameters</b>	
Pixel Pitch	3.9 mm
Pixel Configuration	SMD 3-en-1
Configuration (LxH, per screen)	1024x640 pixels
LED Encapsulation	SMD 1921
Dimensions (W x H x D, per Screen)	4000x2500x97 mm
Diagonal (inch, per screen)	186
Weight (per screen)	420 kg
<b>Optical Parameters</b>	
Equilibrium Brightness	5500 nits
Contrast Ratio	5500:1
Viewing Angle	170°
Bit Depth	8 bits
Color Temperature	6500-10000K
Gray Scale/Colors	16.7M Colors

<b>Electrical Parameters</b>	
Display Working Voltage	AC47~63HZ,220V±15%/110V±15%
Screen - Power Consumption - Max	8000 W
Screen - Power Consumption - Typical	2400 W
Frame Frequency	60 Hz
<b>Operation Conditions</b>	
Working Temperature / Humidity	-10~60 °C / 10%~70% RH
IP Rating	IP65
LED Lifetime	100.000 hours
Refresh Rate	3840 Hz
Video Processor	X6
<b>Certification</b>	
CE	
<b>Service</b>	
Front with locks	
<b>Special Installation</b>	
Cabinets installation side by side	
<b>Accessories</b>	
Decorative frame	