

Niles Landscape Speakers

Impressive Outdoor Listening Built to Last

Whether it's around the pool, patio or picnic table, Niles Landscape Speakers deliver the exceptional Niles indoor audio experience to outdoor locations.

Featuring UV stable fiberglass-reinforced ABS enclosures and weatherproof acoustic components, Niles Landscape speakers are built to last, able withstand even the harshest of climates.

The small form factor of the 4" or 6" satellite speakers seamlessly into into any outdoor space. With 110-degree sound dispersion and the flexibility of both 8 ohm 70V/100V configuration, concert quality audio is now a in any sized backyard.

NI-GS-6 | NI-GS-4



FEATURES

- **Reliability:** Weatherproof fiberglass reinforced ABS enclosures are rugged, ensuring years of reliable performance and able to stand up to weed whackers and outdoor lawn equipment.
- **Enveloping Sound:** A 2-way design with 110-degree wide dispersion brings exceptional clarity and ensures better coverage than traditional outdoor speakers.
- **Versatile Installation:** Low and high impedance capabilities gives flexibility to scale the system to fit any size backyard while adjustable 70V/100V tap setting allows individual volume control of every speaker.
- **Mount where you want:** Ground, surface and conduit mounting is made easy and reliable with quick connect accessories, sold separately.

| |  NI-GS-6 |  NI-GS-4 |
|---------------------------|---|---|
| Woofers | 6" (152mm) Polypropylene Cone with NBR Surround | 4" (100mm) Polypropylene Cone with NBR Surround |
| Tweeter | 3/4" (20mm) Aluminum Dome Tweeter | 3/4" (20mm) Aluminum Dome |
| Enclosure | Weather-Resistant Fiberglass-Reinforced ABS | Weather-Resistant Fiberglass-Reinforced ABS Enclosure |
| Sensitivity | 87dB | 84dB |
| Frequency Response | 105Hz-20kHz +/- 3dB | 115Hz-20kHz +/- 3dB |
| Power Handling | Up to 120W | Up to 90W |
| Nominal Impedance | 8 ohms (in Bypass Mode) | 8 ohms (in Bypass Mode) |
| Tap Settings | 70V/100V: 3.75W (70V only), 7.5W, 15W, 30W, 8 Ohm (Bypass) | Tap Settings: 70V/100V: 3.75W (70V only), 7.5W, 15W, 30W, 8 Ohm (Bypass) |
| Warranty | Limited Lifetime | Limited Lifetime |

SUBWOOFERS AND ACCESSORIES (Sold Separately)



NI-GSBSUB-12

12" (300mm)
In-Ground Subwoofer



NI-GSBSUB-10

10" (250mm)
In-Ground Subwoofer



AW-LS-STAKE

Landscape Speaker
Mounting Stake Accessory



AW-LS-MOUNT

Landscape Speaker
Surface Mount Accessory



AW-LS-CONDUIT

Landscape Speaker Conduit
Box Mounting Accessory